

[Document Name]	Abstract
[Abstract]	
[Objects]	
An organopolysiloxane composition for molding purposes is provided which displays superior mold releasability relative to various resins.	
[Solution Means]	
An organopolysiloxane composition for molding purposes which includes: (A) 100 parts by weight of an organopolysiloxane with at least two alkenyl groups bonded to silicon atoms within a single molecule, (B) a straight chain organopolysiloxane with a hydrogen atom bonded to a silicon atom at both terminals, (C) an organohydrogenpolysiloxane with at least three hydrogen atoms bonded to silicon atoms within a single molecule, (D) an effective quantity of a hydrosilylation reaction catalyst, (E) no more than 50 parts by weight of a finely powdered silica with a specific surface area of at least 50 m <sup>2</sup> /g, and (F) 0 to 20 parts by weight of a non-functional polyorganosiloxane, wherein the total number of hydrogen atoms bonded to silicon atoms within the constituent (B) and the constituent (C) ranges from 1 to 5 per alkenyl group within the constituent (A), and the number of hydrogen atoms bonded to silicon atoms within the constituent (B) accounts for 20 to 70 mol% of the combined number of hydrogen atoms bonded to silicon atoms within the constituent (B) and the constituent (C).	
[Selected Figure]	None